

# SHREE SALASAR

TRADING COMPANY

## PACKAGING SOLUTION



### WE OFFER

Export Container Lashing | Cordstrap Polyester Strapping | Dunnage Air Bags | Cargo Lashing Belts  
Max Stretch Film | Strapping Tools | Warehousing Belts | ODC Cargo Lashing | Container Desiccants  
PET Strapping | Pneumatic Strapping Machine | Semi Automatic Strapping Machine

.... More to Come

Shop No. 1, Shri Krishna Complex, Below Jalaramkrupa Hospital, Vapi Main Road, Silvassa - 396 230. (D.&N.H.)  
Mob.: 9737566724, 9426409866, 7043215810 • E-mail : sstc84@gmail.com

## Container Lashing Service Providers

### Cord Strap Twist Yarn (Heavy Duty)

#### QUALITY

We would like to provide you our company details with immense pleasure. SHREE SALASAR TRADING COMPANY is fast emerging as the company focussed on total cargo securing solutions to solve transit damage problems.

From Co-extruded high tenacity polyester twist yarns embedded in a polymer coating. It is called polyester corded composite strapping due to its composite structure.

Due to its superior properties, composite strapping is preferred for heavy loads and loads carried under difficult conditions.

#### Cord Strap Polyester Coded Composite Strap's Most Important Features :

- High Strength
- Shock Absorbent
- Does not Get Loose (High Retained Tension)
- Highly Elastic and Flexible
- No Sharp Edges That Could Damage Your Products
- Does Not Damage Cargo
- Resistant to Severe Weather Conditions and UV
- Cost-Effective
- Light-Weight
- Rust-Proof, Doesn't Rust or Corrode
- Resistant to Chemicals
- Fast and Easy to Use
- Safe Usage
- Co-Strap Composite
- GL European Certificate
- AAR UK Certificate



## Wide Range of Application Coverage

It is widely used in steel industry, chemical fibre industry, aluminum ingots, paper industry, brick kiln, screw industry, tobacco industry, electronics, textile, machinery and wood industry, etc.

### Cord Strap Twist Yarn (Heavy Duty)

#### Cord Strap Size 13mm, 16mm, 19mm, 25mm, 32mm



## Webbing Polyester Strap & Buckle



## Product Introduction



### Pneumatic Strapping Tool AQD-19

We have now introduced "New Generation Technology Tool" to further cater & support your specific application needs to requirements. Our newest model, AQD-19 is new generation technology tool designed specially for heavy duty & rugged performance. The new AQD-19 is developed with high quality durable parts specially imported from "JAPAN" & "KOREA" in order to have minimum & low maintenance and have longer life.

- Pneumatic strapping machine is the packing machine for polyester (PET)
- They can be widely used in many industries including paper, wood packing, stone packing, steel pipe packing, cotton packing, used cloth packing, fibre packing and so on.

\* Please use are male-female connector and FRL for best results.

## Product Specification

### MODEL : AQD-19

- Tension force of binding band  
(when input air pressure is 0.63MPa): 3500N
- Max allowable working pressure : 0.5-0.7 MPA (72-100Psi)
- Ideal working pressure : 0.63 Map
- Weight f packaging machine : 3.5 kg
- Total length : 278.5mm (Base : 70mm)
- Width : 149.5mm / Hight : 173mm
- Material of packaging belt : Pet Strep
- Width of packaging belt : 13mm-19mm
- Thickness packaging belt : 0.5-1.5mm
- Allowable lubrication oil : 51#
- Vibration quantity : Meet requirement of IOS5349
- Consumption of compressed air : 0.3/Min
- Adjusting scope of fusion time : 2-5s

## SSTC AS 50 C Semi Automatic Strapping Machine



- Quality Product Supply Only
- New Technology Machine
- Tow DC Motor
- 70% Power Saving
- 65% Maintenance Saving
- Experience Warranty

|                                    |                                                                                   |
|------------------------------------|-----------------------------------------------------------------------------------|
| Model                              | AS-50C                                                                            |
| Power Source                       | 110-120/200-240V 50/60Hz 1 PH<br>0.25kW 2.5A                                      |
| Packing Speed                      | ≤3 Second/Path                                                                    |
| Tension Range                      | 5kg-50kg                                                                          |
| Hot-Adhering Position              | Bottom                                                                            |
| Working Table Height               | 730mm                                                                             |
| Min. Packaging Size                | 60mm*60mm                                                                         |
| Applicable PP Strap                | Width : 5mm-15mm,<br>Thickness : 0.5mm-085mm                                      |
| Applicable PP Strap Spool          | Inner Dia : 200mm~210mm,<br>Outer Dia : 400mm~500mm,<br>Width : 160mm~ 190mm      |
| Packing Type                       | Manual Semi-Automatic Packing                                                     |
| Electrical Configuration           | P.C. Board Control<br>Electrical : Switching Power Supply<br>Motor : DC Motor 24V |
| Machine Size                       | L850mm x W545mm x H730mm                                                          |
| Shipping Size                      | L870mm x W560mm x H780mm                                                          |
| Weight                             | N.W : 80kg G.W : 90kg                                                             |
| Environment Moisture               | 35%-85%RH                                                                         |
| Transportation/Storage Temperature | -250C-550C                                                                        |
| Bottom Adhesion                    | Surface≥90%, Width≥20%,<br>Deviation of Position≤2mm                              |

### Machine Features:

1. Semi-Automatic Strapping Machine for PP Strapping Material.
2. Tough and Compact Construction with a Small Footprint.
3. Simple, Safe and User-Friendly Operation.
4. Mobile with High Capacity Strap Reel.
5. Strap Tension Adjustable From Soft to High.

\* Electrical Earthing Proper Required

## Stretch Wrapping New Technology Machine

### MH-FG-2000A Mechanical Stretch

### MH-FG-2000B Power Pre-Stretch Automatic Pallet Stretch Wrapper

Best Quality Electric Parts Soft Start/Stop, Home Position, PLC Control, Reliable Performance, Easy Operation Sensor Test Pallet Height

- **Power Voltage**  
1 P AC 220/111V 50/60 Hz 1.0/1.25kw
- **Speed of Turntable**  
0~10r/min Dia. of Turntable  
  
ø 1500mm (Optionalø1650/ø1800/ø2000/ø2200)
- **Mast Height**  
H2400mm (Optional 2000/2700/3000/3200/3400)
- **Film**  
LLDPE Film, Width<=500mm, out diameter<=280mm
- **Capacity**  
ø 1500mm : 1500 kg, ≥ ø 1650 mm : 2000 kg
- **Package Size** ≥2650x1650x800mm
- **Noise**≤75DB
- **Surroundings**  
Humidity≤98%, Temperature-100C-400C
- **Lubricating Material**  
Common Lubricating Grease
- **Optional**  
Ramp Panel LCD Control Box Magnetic Clutch
- **Electrical Specification**
  - PLC : Koran LG
  - Inverter : French Schneider
  - Travel Switch : French Schneider
  - Button Switch : French "TE"
  - Connector : French "TE"
  - Sensor : German Technology
  - Motor : Meiwa



## OUR PRODUCT

### Polyester CordLashing



Size : 25mm to 50mm  
Strength : 2 Tons to 5 Tons

### Polyester CordStrap



Size : 9mm to 32mm

### Polyester Pet Strap



Size : 11mm to 19mm  
Strap Thickness : 0.40mm to 1.27mm

### Cord Strap Buckles



Size : 9mm to 50mm  
Extra Heavy Duty Industrial Grade

### Stretch Film



Size : 12mic to 29mic  
Manual & Machine Grade (Important)

### Edge & Core Protector



Size : 40mm to 100mm  
Extra Heavy Duty Industrial Grade

### Strapping Dispensers



### Cord Strap Lashing Tool



Size : 19mm to 50mm  
Extra Heavy Duty Industrial Grade

### Manual Strapping Tool



Size : 19mm to 50mm  
Extra Heavy Duty Industrial Grade

### Manual Strapping Tool



Size : 12mm to 19mm  
Heavy Duty Industrial Grade

### Pneumatic Pet Strapping Tool



Size : 12mm to 19mm  
Strap Thickness : 0.5mm to 1.27mm

### Battery Powered Strapping Tool



Size : 12mm to 19mm  
Strap Thickness : 0.5mm to 1.27mm

### Dunnage-AIR-Bags



Extra Heavy Duty Industrial Grade

### Semi Automatic Strapping Machine



### PALLET PACKING

