

POLYESTER (PET) STRAP - SIZE & SPECIFICATION

SHREE SALASAR TRADING COMPANY

PET STRAP (PLAIN / SMOOTH)

Sr. No.	Width	Thickness	Weight per meter	Runnage meter per Kg.	Minimum Breaking strength		Elongation at break
	mm	mm	Gram	Meter	N	Kgf	%
1	12 (11.70 to 12.10)	0.50 (0.48 to 0.52)	8.10	123.00		250	25
2	12 (11.70 to 12.10)	0.60 (0.58 to 0.62)	9.70	103.00		250	"
3	12 (11.70 to 12.10)	0.65 (0.63 to 0.67)	10.50	95.00		300	"
4	12 (11.70 to 12.10)	0.70 (0.68 to 0.72)	11.30	88.00		300	"
5	12 (11.70 to 12.10)	0.80 (0.78 to 0.82)	12.90	77.00		350	"
6	15 (14.70 to 15.10)	0.60 (0.58 to 0.62)	12.10	82.00		350	"
7	15 (14.70 to 15.10)	0.70 (0.68 to 0.72)	14.10	71.00		400	"
8	15 (14.70 to 15.10)	0.80 (0.78 to 0.82)	16.10	62.00		450	"
9	15.50 (15.30 to 15.60)	0.90 (0.88 to 0.92)	18.70	53.00		600	"
10	16 (15.70 to 16.10)	0.90 (0.88 to 0.92)	19.30	52.00		600	"
11	16 (15.70 to 16.10)	1.00 (0.98 to 1.02)	21.50	46.00		550	"
12	19 (18.70 to 19.10)	0.70 (0.68 to 0.72)	17.80	56.00		500	"
13	19 (18.70 to 19.10)	0.80 (0.78 to 0.82)	20.40	49.00		550	"
14	19 (18.70 to 19.10)	1.00 (0.98 to 1.02)	25.50	39.00		700	"
15	19 (18.70 to 19.10)	1.27 (1.25 to 1.29)	32.40	30.00		850	"

SHREE SALASAR TRADING COMPANY

PET STRAP (EMBOSSSED / KNURL)

Sr. No.	Width	Thickness	Weight per meter	Runnage meter per Kg.	Minimum Breaking strength		Elongation at break
	mm	mm	Gram	Meter	N	Kgf	%
1	12 (11.70 to 12.10)	0.50 (0.48 to 0.52)	7.60	131.00		220	25
2	12 (11.70 to 12.10)	0.55 (0.53 to 0.57)	8.30	120.00		300	"
3	12 (11.70 to 12.10)	0.60 (0.58 to 0.62)	8.60	116.00		300	"
4	12 (11.70 to 12.10)	0.65 (0.63 to 0.67)	9.40	106.00		300	"
5	12 (11.70 to 12.10)	0.70 (0.68 to 0.72)	10.20	98.00		320	"
6	12 (11.70 to 12.10)	0.80 (0.78 to 0.82)	11.60	86.00		320	"
7	15 (14.70 to 15.10)	0.60 (0.58 to 0.62)	11.20	89.00		300	"
8	15 (14.70 to 15.10)	0.70 (0.68 to 0.72)	12.80	78.00		350	"
9	15 (14.70 to 15.10)	0.80 (0.78 to 0.82)	14.80	67.00		400	"
10	15.50 (15.30 to 15.60)	0.90 (0.88 to 0.92)	17.50	57.00		500	"
11	16 (15.70 to 16.10)	0.70 (0.68 to 0.72)	13.70	73.00		400	"
12	16 (15.70 to 16.10)	0.80 (0.78 to 0.82)	15.80	63.00		450	"
13	16 (15.70 to 16.10)	0.90 (0.88 to 0.92)	17.90	56.00		550	"
14	16 (15.70 to 16.10)	1.00 (0.98 to 1.02)	20.00	50.00		600	"
15	19 (18.70 to 19.10)	0.70 (0.68 to 0.72)	16.30	61.50		500	"
16	19 (18.70 to 19.10)	0.80 (0.78 to 0.82)	18.80	53.00		550	"
17	19 (18.70 to 19.10)	1.00 (0.98 to 1.02)	23.80	42.00		700	"
18	19 (18.70 to 19.10)	1.27 (1.25 to 1.29)	30.40	33.00		900	"