

SHREE SALASAR

TRADING COMPANY

PACKAGING SOLUTION



WE OFFER

Export Container Lashing | Cordstrap Polyester Strapping | Dunnage Air Bags | Cargo Lashing Belts
Max Stretch Film | Strapping Tools | Warehousing Belts | ODC Cargo Lashing | Container Desiccants
PET Strapping | Pneumatic Strapping Machine | Semi Automatic Strapping Machine

.... More to Come

Shop No. 1, Shri Krishna Complex, Below Jalaramkrupa Hospital, Vapi Main Road, Silvassa - 396 230. (D.&N.H.)
Mob.: 9737566724, 9426409866, 7043215810 • E-mail : sstc84@gmail.com

Container Lashing Service Providers

Cord Strap Twist Yarn (Heavy Duty)

QUALITY

We would like to provide you our company details with immense pleasure. SHREE SALASAR TRADING COMPANY is fast emerging as the company focussed on total cargo securing solutions to solve transit damage problems.

From Co-extruded high tenacity polyester twist yarns embedded in a polymer coating. It is called polyester corded composite strapping due to its composite structure.

Due to its superior properties, composite strapping is preferred for heavy loads and loads carried under difficult conditions.

Cord Strap Polyester Coded Composite Strap's Most Important Features :

- High Strength
- Shock Absorbent
- Does not Get Loose (High Retained Tension)
- Highly Elastic and Flexible
- No Sharp Edges That Could Damage Your Products
- Does Not Damage Cargo
- Resistant to Severe Weather Conditions and UV
- Cost-Effective
- Light-Weight
- Rust-Proof, Doesn't Rust or Corrode
- Resistant to Chemicals
- Fast and Easy to Use
- Safe Usage
- Co-Strap Composite
- GL European Certificate
- AAR UK Certificate



Wide Range of Application Coverage

It is widely used in steel industry, chemical fibre industry, aluminum ingots, paper industry, brick kiln, screw industry, tobacco industry, electronics, textile, machinery and wood industry, etc.

Cord Strap Twist Yarn (Heavy Duty)

Cord Strap Size 13mm, 16mm, 19mm, 25mm, 32mm



Webbing Polyester Strap & Buckle



Product Introduction



Pneumatic Strapping Tool AQD-19

We have now introduced "New Generation Technology Tool" to further cater & support your specific application needs to requirements. Our newest model, AQD-19 is new generation technology tool designed specially for heavy duty & rugged performance. The new AQD-19 is developed with high quality durable parts specially imported from "JAPAN" & "KOREA" in order to have minimum & low maintenance and have longer life.

- Pneumatic strapping machine is the packing machine for polyester (PET)
- They can be widely used in many industries including paper, wood packing, stone packing, steel pipe packing, cotton packing, used cloth packing, fibre packing and so on.

* Please use are male-female connector and FRL for best results.

Product Specification

MODEL : AQD-19

- Tension force of binding band (when input air pressure is 0.63MPa): 3500N
- Max allowable working pressure : 0.5-0.7 MPA (72-100Psi)
- Ideal working pressure : 0.63 Map
- Weight f packaging machine : 3.5 kg
- Total length : 278.5mm (Base : 70mm)
- Width : 149.5mm / Hight : 173mm
- Material of packaging belt : Pet Strep
- Width of packaging belt : 13mm-19mm
- Thickness packaging belt : 0.5-1.5mm
- Allowable lubrication oil : 51#
- Vibration quantity : Meet requirement of IOS5349
- Consumption of compressed air : 0.3/Min
- Adjusting scope of fusion time : 2-5s

SSTC AS 50 C Semi Automatic Strapping Machine



- Quality Product Supply Only
- New Technology Machine
- Tow DC Motor
- 70% Power Saving
- 65% Maintenance Saving
- Experience Warranty

Model	AS-50C
Power Source	110-120/200-240V 50/60Hz 1 PH 0.25kW 2.5A
Packing Speed	≤3 Second/Path
Tension Range	5kg-50kg
Hot-Adhering Position	Bottom
Working Table Height	730mm
Min. Packaging Size	60mm*60mm
Applicable PP Strap	Width : 5mm-15mm, Thickness : 0.5mm-085mm
Applicable PP Strap Spool	Inner Dia : 200mm~210mm, Outer Dia : 400mm~500mm, Width : 160mm~ 190mm
Packing Type	Manual Semi-Automatic Packing
Electrical Configuration	P.C. Board Control Electrical : Switching Power Supply Motor : DC Motor 24V
Machine Size	L850mm x W545mm x H730mm
Shipping Size	L870mm x W560mm x H780mm
Weight	N.W : 80kg G.W : 90kg
Environment Moisture	35%-85%RH
Transportation/Storage Temperature	-250C-550C
Bottom Adhesion	Surface≥90%, Width≥20%, Deviation of Position≤2mm

Machine Features:

1. Semi-Automatic Strapping Machine for PP Strapping Material.
2. Tough and Compact Construction with a Small Footprint.
3. Simple, Safe and User-Friendly Operation.
4. Mobile with High Capacity Strap Reel.
5. Strap Tension Adjustable From Soft to High.

* Electrical Earthing Proper Required

Stretch Wrapping New Technology Machine

MH-FG-2000A Mechanical Stretch

MH-FG-2000B Power Pre-Stretch Automatic Pallet Stretch Wrapper

Best Quality Electric Parts Soft Start/Stop, Home Position, PLC Control, Reliable Performance, Easy Operation Sensor Test Pallet Height

- **Power Voltage**
1 P AC 220/111V 50/60 Hz 1.0/1.25kw
- **Speed of Turntable**
0~10r/min Dia. of Turntable

ø 1500mm (Optionalø1650/ø1800/ø2000/ø2200)
- **Mast Height**
H2400mm (Optional 2000/2700/3000/3200/3400)
- **Film**
LLDPE Film, Width<=500mm, out diameter<=280mm
- **Capacity**
ø 1500mm : 1500 kg, ≥ ø 1650 mm : 2000 kg
- **Package Size** ≥2650x1650x800mm
- **Noise**≤75DB
- **Surroundings**
Humidity≤98%, Temperature-100C-400C
- **Lubricating Material**
Common Lubricating Grease
- **Optional**
Ramp Panel LCD Control Box Magnetic Clutch
- **Electrical Specification**
 - PLC : Koran LG
 - Inverter : French Schneider
 - Travel Switch : French Schneider
 - Button Switch : French "TE"
 - Connector : French "TE"
 - Sensor : German Technology
 - Motor : Meiwa



OUR PRODUCT

Polyester CordLashing



Size : 25mm to 50mm
Strength : 2 Tons to 5 Tons

Polyester CordStrap



Size : 9mm to 32mm

Polyester Pet Strap



Size : 11mm to 19mm
Strap Thickness : 0.40mm to 1.27mm

Cord Strap Buckles



Size : 9mm to 50mm
Extra Heavy Duty Industrial Grade

Stretch Film



Size : 12mic to 29mic
Manual & Machine Grade (Important)

Edge & Core Protector



Size : 40mm to 100mm
Extra Heavy Duty Industrial Grade

Strapping Dispensers



Cord Strap Lashing Tool



Size : 19mm to 50mm
Extra Heavy Duty Industrial Grade

Manual Strapping Tool



Size : 19mm to 50mm
Extra Heavy Duty Industrial Grade

Manual Strapping Tool



Size : 12mm to 19mm
Heavy Duty Industrial Grade

Pneumatic Pet Strapping Tool



Size : 12mm to 19mm
Strap Thickness : 0.5mm to 1.27mm

Battery Powered Strapping Tool



Size : 12mm to 19mm
Strap Thickness : 0.5mm to 1.27mm

Dunnage-AIR-Bags



Extra Heavy Duty Industrial Grade

Semi Automatic Strapping Machine



PALLET PACKING

